



Product Data

Vanellus C3 Mono 50

Diesel Engine Oil

Description

BP Vanellus C3 Mono 50 is designed for use in a variety of applications that require a monograde engine oil.

Application

BP Vanellus C3 Mono 50 is primarily for use naturally aspirated and turbocharged diesel engines but can also be used in some four-stroke gasoline engines where a monograde oil is recommended. It may also be used in certain transmission applications where a monograde engine oil is recommended.

Advantages

BP Vanellus Mono 50 offers the following benefits:

- Enhanced engine cleanliness - provides reliable engine performance and peace of mind against breakdown
- Protection against wear and deposits
- Complete shear stability for 'stay in grade' optimum performance

Typical Characteristics

Name	Method	Units	Vanellus C3 Mono 50
Density @ 15C	ASTM D4052	g/ml	0.899
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	16.9
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	182
Viscosity Index	ASTM D2270	None	98
Ash, Sulphated	ASTM D874	% wt	1.38
Total Base Number, TBN	ASTM D2896	mg KOH/g	10.2
Pour Point	ASTM D97	°C	-30

Product Performance Claims

API CF/SF

Vanellus C3 Mono 50

25 Apr 2014

BP, the BP logo and related marks are trademarks of BP p.l.c., used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Middle East, Standard Chartered Tower, 8th Floor, Down Town Burj Khalifa, By Emaar Square , P.O. Box 1699, Dubai, United Arab Emirates
Lubricants UK Telephone: 01793 512712, Automotive Technical Helpline: 0845 082 1719 Orders/Enquiries: 0845 6008125
www.bp.com