



Product Data Sheet

BP Visco 2000 20W-50 CleanGuard™ Engine Protection Technology

Description

Cleaner engines last longer and run better.

BP Visco's CleanGuard™ Engine Protection Technology keeps your engine cleaner and fights all dirt, varnish and even deadly sludge in vital oil ways.

Visco's components slow the formation of dirt at its source and wrap up dirt particles so they will not stick to critical engine components.

Application

BP Visco 2000 20W-50 is suitable for use in automotive gasoline and CNG fuel engines where the manufacturer recommends an API SJ or earlier specification 20W-50 lubricant.

Advantages

BP Visco 2000 20W-50 is a premium quality engine oil which provides:

- Proven engine cleanliness
- Reliable engine protection for normal driving conditions
- Reduced oil burnoff

Typical Characteristics

Name	Method	Units	BP Visco 2000 20W-50
Density @ 15C, Relative	ASTM D4052	g/ml	0.89
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	19.1
Viscosity, CCS -15C	ASTM D5293	mPa.s (cP)	8860
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	174
Viscosity Index	ASTM D2270	None	124
Ash, Sulphated	ASTM D874	% wt	0.735
Pour Point	ASTM D97	°C	-30
Flash Point, PMCC	ASTM D93	°C	212

Product Performance Claims

API SJ

BP Visco 2000 20W-50

29 Mar 2015

BP, the BP logo and related marks are trademarks of BP p.l.c., used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Middle East, Standard Chartered Tower, 8th Floor, Down Town Burj Khalifa, By Emaar Square , P.O. Box 1699, Dubai, United Arab Emirates
Technical / Customer Service: +9714-3317999
www.bp.com