



Product Data

BP Visco 3000 20W-50

Cleanguard Engine Protection Technology

Description

Cleaner engines last longer and run better.

BP Visco's Cleanguard Engine Protection Technology keeps your engine up to 30% cleaner* and fights all dirt - varnish, carbon, even deadly sludge in vital oilways.

Visco's ingredients slow the formation of dirt at its source and wrap up dirt particles so they cannot stick to sensitive engine parts.

* vs API SL requirements, piston cleanliness in ASTM Sequence III test limit

Application

Visco 3000 20W/50 is suitable for use in automotive gasoline and diesel vehicles where the manufacturer recommends an API SL/CF or earlier specification 20W-50 lubricant.

Advantages

BP Visco 3000 20W-50 is a premium quality engine oil which provides :

- Keeps your engine up to 30% cleaner*
- Advanced protection for normal driving conditions
- Reduced oil burnoff
- Superior anti-wear performance

* vs API SL requirements, piston cleanliness in ASTM Sequence III test limit

Typical Characteristics

Name	Method	Units	BP Visco 3000 20W-50
Density @ 15C, Relative	ASTM D4052	g/ml	0.89
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	19.1
Viscosity, CCS -15C	ASTM D5293	mPa.s (cP)	9000
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	173
Viscosity Index	ASTM D2270	None	125
Ash, Sulphated	ASTM D874	% wt	0.88
Pour Point	ASTM D97	°C	-30
Flash Point, PMCC	ASTM D93	°C	210

Product Performance Claims

API SL/CF

BP Visco 3000 20W-50

25 Apr 2014

BP, the BP logo and related marks are trademarks of BP p.l.c., used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Middle East, Standard Chartered Tower, 8th Floor, Down Town Burj Khalifa, By Emaar Square , P.O. Box 1699, Dubai, United Arab Emirates
Lubricants UK Telephone: 01793 512712, Automotive Technical Helpline: 0845 082 1719 Orders/Enquiries: 0845 6008125
www.bp.com