



Product Data Sheet

BP Visco CNG 20W-50 CleanGuard Engine Protection Technology

Description

BP Visco CNG 20W-50 with CleanGuard™ Engine Protection Technology is a superior quality multigrade engine oil developed by BP for all year round use in dedicated CNG engines and dual fuel engines under all driving conditions.

It provides high levels of protection against wear, corrosion, deposit formation and keeps the engine cool at the same time.

Its' viscosity index improver ensures full multigrade performance between services.

Application

BP Visco CNG 20W-50 is suitable for use in automotive CNG and dual fuel engines where the manufacturer recommends an API SG or earlier specification 20W-50 lubricant.

Advantages

BP Visco CNG 20W-50:

- Proven engine protection
- Keeps your engine cool
- Helps prolong engine life

Typical Characteristics

Name	Method	Units	BP Visco CNG 20W-50
Density @ 15C, Relative	ASTM D4052	g/ml	0.890
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	17.4
Viscosity, CCS -15C (20W)	ASTM D5293	mPa.s (cP)	8900
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	159
Viscosity Index	ASTM D2270	None	119
Pour Point	ASTM D97	°C	-24
Flash Point, PMCC	ASTM D93	°C	211
Ash, Sulphated	ASTM D874	% wt	0.7

Product Performance Claims

API SG

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

BP Visco CNG 20W-50

22 Mar 2015

BP, the BP logo and related marks are trademarks of BP p.l.c., used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Middle East, Standard Chartered Tower, 8th Floor, Down Town Burj Khalifa, By Emaar Square , P.O. Box 1699, Dubai, United Arab Emirates
Technical / Customer Service: +9714-3317999
www.bp.com